




Portable Digital Gas Flow Meter

**GF 1010** 



The new pocket sized GF 1010 gas flow meter makes gas flow measurement easier and more accurate, helping to eliminate user errors. The GF 1010 is an essential tool for troubleshooting and routine maintenance of your gas chromatograph. The LCD display with back light makes reading flows clear and easy. As an option, there is a Silicone protection cover available to protect the flowmeter.

## **Specifications**

Flow Range: 0.5 - 1200 ml/min

No need to select a gas type due to volume flow meter technique.

Mixed gas can also be measured.

Accuracy:  $\pm 3\%$  or  $\pm 0.3$  mL/min whichever is geater (for calibration gas N2)

Operating temp. range: 10 - 40°C (Accuracy Range 15 - 30°C)

Silicone tube: I.D. = 3mm, O.D. = 7mm (maxiumum temperature = 200°C)
Measurable gases: N2, Air, He, Ar, H2, etc. (no corrosive and humidity gas)

Battery: 2 AA Batteries
Display: LCD with back light
Standards: WEEE, RoHS, CE

Dimensions: 76mm(W)×135mm(D)×35mm(H)
Weight: approx. 240 gram without battery

Functions: Zero Adjustment, Battery indicator, selectable auto power off

## **Options and Part Numbers**

2709-10100, Gas Flow Meter GF 1010 (includes battery, tube and manual) Options:

2709-10102, GF 1010 replacement Silicone Tube

2709-10110, Silicone Cover (Navy Blue)

2709-10103, TCD Vent Adaptor (1/8" Swagelok Adaptor)

2709-55015, Capillary Column Adaptor





Capillary Column Adaptor option



GF 1010 with Silicone Cove

## **Worldwide Ordering Information**

<u>GL Sciences, Inc. Japan</u> 22-1 Nishishinjuku 6-Chome Shinjuku Tokya 163-1130, Japan. Chromatography World
217, Chamapaklal Industrial Area,
2nd Floor, Sion East, Mumbai-400022.

Phone: 022-43159127

Email: <a href="mailto:speed@chromatographyworld.com">speed@chromatographyworld.com</a> <a href="https://www.chromatographyworld.com">www.chromatographyworld.com</a>

Hyderabad | Ahmedabad | Bangalore | Chennai | Chandigarh | Dehradun | Delhi | Goa | Indore | Kolkata | Pune | Surat