



DIGITAL FUEL NOZZLE WITH METER/DIGITAL METERING FUEL NOZZLE/AUTOMATIC FUEL NOZZLE WITH DIGITAL METER



TECHNICAL SPECIFICATIONS:

Measurement System

Resolution (Nominal): High Flow: 0.01 lit/pulse

: Low Flow: 0.005 lit/pulse

Flow Rate (Range): ALSURFACE WITHOUT OXIDED TREATMENT (10-90 Ltr/minute for Diesel, Gasoline, Kerosene)

Operating Pressure: 0.15-0.3Mpa Bursting

Pressure (min): 0.2Mpa

Storage Temperature: (Range): -20 -- 70 (c) Storage

HESHAM INDUSTRIAL SOLUTIONS, 112 BRIJ INDUSTRIES, NR BUNDY INDIA, GIDC
MAKARPURA, VADODARA, GUJARAT-390010, INDIA, GST: 24AZCPM3892K1Z1
Our Website: www.heshamsolutions.com , www.heshamsolutions.in
Mob: 7228866734, contact@heshamsolutions.com, heshamsolutions@gmail.com



HESHAM INDUSTRIAL SOLUTIONS



Humidity (Max): 95 (%RU) Operating Temperature: -10 → + (c)

Flow Resistance: 0.30 Bar at 100 lit/min Viscosity (Range): 2 –

5.35 cSt

Accuracy: ± 1% after calibration within 10-90 (lit/min) 2,65 -23,8 (gallons/min) Range

Reproducibility (Typical): ± 0.3 (%)

Power Supply: 1 *Cr2032/3V Lithium Button Cell Battery Flow rated 35

l/min, min. 25 l/min, max. 60 l/min Battery Life: 18 – 36 Months

Weight: 1.5kg (N.W) Protection: IP55



HESHAM INDUSTRIAL SOLUTIONS, 112 BRIJ INDUSTRIES, NR BUNDY INDIA, GIDC
MAKARPURA, VADODARA, GUJARAT-390010, INDIA, GST: 24AZCPM3892K1Z1
Our Website: www.heshamsolutions.com , www.heshamsolutions.in
Mob: 7228866734, contact@heshamsolutions.com, heshamsolutions@gmail.com