

# Mounted Disc Plough (Tubular Frame)

B.L Agriculture



## FEATURES

- In conformity with the soil conditions it is being produced with 2-3-4-5 and 6 Disc (Bottom) version with an option for extra kit for converting it to extra disc plough.
- It is directly mounted to the tractors.
- The extra heavy-duty seamless tubing frame has high trash clearance allowing the plough to operate under heavy crop residue.

## Mounted Disc Plough (Tubular Frame)

SIZE	2 BOTTOM	3 BOTTOM	4 BOTTOM	5 BOTTOM (4+1)
FRAME	Heavy Duty seamless Tubular Frame (OD 168 mm with 8 mm thickness)	Heavy Duty seamless Tubular Frame (OD 168 mm with 10 mm thickness)	Heavy Duty seamless Tubular Frame (OD 168 mm with 10 mm thickness)	Heavy Duty seamless Tubular Frame (OD 168 mm with 12 mm thickness)
MOUNTED	CAT - II	CAT - II	CAT - II	CAT - II
LENGTH	1800 mm	2400 mm	3000 mm	3600 mm
WIDTH	825 mm	1050 mm	1250 mm	1500 mm
HEIGHT	1200 mm	1225 mm	1250 mm	1250 mm
DISCS	660 x 6 mm Boron steel	660 x 6 mm Boron steel	660 x 6 mm Boron steel	660 x 6 mm Boron steel
DISC SPACING	550 mm	550 mm	575 mm	575 mm
COLTER DISC	500 x 6 mm boron steel	500 x 6 mm boron steel	500 x 6 mm boron steel	500 x 6 mm boron steel
SCRAPPER	6 mm adjustable	6 mm adjustable	6 mm adjustable	6 mm adjustable
BEARINGS	2 Nos. Taper roller	2 Nos. Taper roller	2 Nos. Taper roller	2 Nos. Taper roller
WIDTH OF CUT	500 - 550 mm	875 - 925 mm	1150 - 1200 mm	1575 - 1625 mm
REQUIRED TRACTOR	40 - 45 HP	50 - 60 HP	70 - 80 HP	90 HP & Above
APPROX.WEIGHT	275 Kg.	400 Kg.	500 Kg.	600 Kg.

F-829, Near Mercedes service center Sitapura Industrial Area, Jaipur, RAJ.

Email- [blagriculture@gmail.com](mailto:blagriculture@gmail.com)

9414018891,9462573334

