

Heavy Duty Mounted Cum Trailed Offset Disc Harrow

B.L Agriculture



FEATURES

- In conformity with the soil conditions it is being produced with 2-3 & 4 version with an option for extra kit for converting it to extra disc plough.
 - It is directly mounted to the tractors.
- The extra heavy-duty seamless tubing frame has high trash clearance allowing the plough to operate under heavy crop residue

SPECIFICATIONS	8X8	9X9	10X10
FRAME	Square Box Frame	Square Box Frame	Square Box Frame
GANG BOLT	32 mm Central square Solid Bar With Split Gangs	32 mm Central square Solid Bar With Split Gangs	32 mm Central square Solid Bar With Split Gangs
LENGTH	1875 mm	1875 mm	1875 mm
WIDTH	1875 mm	2100 mm	2325 mm
NO. OF DISCS	16	18	20
TYPE OF DISC	Notched (Front / Rear) Plane Optional	Notched (Front / Rear) Plane Optional	Notched (Front / Rear) Plane Optional
DISC DIAMETER	560 mm	560 mm	560 mm
WIDTH OF CUT	1775 mm	2000 mm	2250 mm
DISTANCE BETWEEN DISCS	225 mm	225 mm	225 mm
BEARING HUBS	8 with Taper Roller Bearing	8 with Taper Roller Bearing	8 with Taper Roller Bearing
ALL OVER HEIGHT	1100 mm	1100 mm	1100 mm
REQUIRED POWER HP	45 Hp & Above	50 Hp & Above	55 Hp & Above
APPROX. WEIGHT	580 Kg.	610 Kg.	640 Kg.

F-829,3rd phase Near Mercedes service center
Sitapura Industrial Area, Jaipur, RAJ.

Email- blagriculture@gmail.com
9414018891,9462573334