PVC BRAIDED WATER HOSE


PVC BRAIDED WATER HOSE(CODE : BGH)			
INCH	MM	APRX.WEIGHT	METERS
1/2"	12	4.200 KGS	30.000
3/4"	20	6.200 KGS	30.000
1"	25	9.000 KGS	30.000
1-1/4"	32	15.000 KGS	30.000





PVC	PVC BRAIDED WATER HOSE (CODE: ABH)				
INCH	MM	APRX. WEIGHT METERS			
1/2"	12	4.200 KGS	30.000		
3/4"	20	6.200 KGS	30.000		
1"	25	9.100 KGS	30.000		
1-1/4"	32	15.000 KGS	30.000		

PVC BRAIDED WATER HOSE (EXTRA HEAVY) BETTAR USE FOR CONSTRUCTION INCH MM APRX. WEIGHT METERS 3/4" 20 8 TO 8.500 30.000 1" 25 12 TO 15 30.000







Structure:

 Specialized Virgin Material Cristal Clear shining and Smooth finishing.

Application:

- Water hose is superior quality pressure rating.
- Mainly use of water supply to Irrigation, Gardening and cleaning.

Advantage:

- Very light in weight hence low migration property.
- Longer shell life.
- Highly meets the International standard of Quality.
- leack Proof and Durable Quality

Other Colors:

- Available also in other colors.
- Please ask the company for minimum quantity.
- Special size or coil length request to be satisfied upon agreement with Tirupati Polyflex.
- All Technical data available are subject to modification without prior notice.

PVC AIR HOSE

PVC BRAIDED AIR HOSE				
SIZE IN INCH	SIZE IN MM	WALL THICKNESS MM	WORKING PRESSURE KGS/CM2	LENGTH METERS
1/4"	6	3.00	25.00	100
5/16"	8	3.00	25.00	100
3/8"	10	3.50	25.00	100
1/2"	12	3.50	20.00	100
5/8"	15	3.50	20.00	100/50/30
3/4"	20	4.00	20.00	100/50/30
1"	25	4.80	15.00	100/50/30
1-1/4"	31	4.80	15.00	50/30
1-1/2"	40	5.00	15.00	50/30
2	50	6.00	10.00	50/30









Structure:

 Specialized virgin Material Cristal Clear Shining and Smooth finishing.

Application:

- Braided Air Hose offers higher pressure capability than PVC Tubing.
- Its Mirror smooth interior allows constant flow of Water & Air without any obstacles.
- Advantage:
- Very light in weight hence low migration property.
- longer shell life.
- Highly meets the International standard of Quality.
- leack Proof and Durable Quality.
- Other Colors:
- Available also in other colors.
- Please ask the company for minimum quantity.
- Recommanded Maximum working Temperature 55/60 C0
- Special size or coil length request tobe satisfied upon agreement with Tirupati Polyflex.
- All Technical data available are subject to modification without prior notice.

PVC WELDING HOSE

PVC WELDING HOSE				
SIZE	SIZE	WALL THICKNESS	WORKING	LENGTH
IN	IN	MM	PRESSURE	METERS
INCH	MM		KGS/CM2	
1/4"	8	3.00	25.00	50/100
5/16"	10	3.50	25.00	50/100



PVC BRAIDED CAR WASHING HOSE				
SIZE	SIZE	WALL THICKNESS	WORKING	LENGTH
IN	IN	MM	PRESSURE	METERS
INCH	MM		KGS/CM2	
5/16"	10	5.00	40.00	50/100
1/2"	12	5.50	30.00	50/100







Structure:

 Specialized Virgin Material Cristal Clear shining and smooth finishing.

Application:

- Welding Hose meets various requirements of clients like, Welding, Cutting and bonding.
- Also useful for Industrial workshops, Ship breaking other service station and Garage.
- Recommanded Maximum working temperature 65/70 C0

Structure:

 Specialized Virgin Material Cristal Clear Shining and smooth finishing

Application:

• Mostly useful in Vehicle service Station.

Other Colors:

- Available also in other colors.
- Please ask the company for minimum quantity requirements and pricing.
- Special size or coil length request tobe satisfied upon agreement with Tirupati Polyflex.
- All Technical data available are subject to modification without prior notice.