



An **ISO 9001:2015**
CERTIFIED CO.

INCUBATOR SHAKER

Precision. Reliability. Performance.

ESEL Incubator Shaker is designed for precise temperature control and consistent shaking motion, ideal for a wide range of laboratory applications including microbiology, biotechnology, cell culture, and more.



PRECISE
TEMPERATURE
CONTROL



CONSISTENT
SHAKING
MOTION



DURABLE &
RELIABLE
DESIGN



WIDE RANGE
OF LAB
APPLICATIONS



SPECIFICATIONS

Model	Incubator Shaker
Temperature Range	Ambient +5°C to 60°C
Temperature Accuracy	±0.5°C
Temperature Control	Digital PID Controller
Shaking Speed Range	20 to 250 RPM
Speed Accuracy	±1 RPM
Shaking Motion	Orbital
Orbit Diameter	20 mm
Timer Range	0 to 120 Minutes
Display	Digital
Interior Material	Stainless Steel
Exterior Material	Powder Coated Mild Steel
Door	Insulated with Viewing Window
Safety Features	Over Temperature Protection, Motor Overload Protection
Power Supply	220-240V, 50Hz
Power Consumption	800 Watt (Approx.)
Optional	Programmable Controller, RS-232 Interface, UV Light

*Specifications are subject to change without prior notice.

APPLICATIONS

- Microbiology & Cell Culture
- Biotechnology & Molecular Biology
- Enzyme Studies
- Plant Tissue Culture
- General Laboratory Applications

KEY FEATURES

- ✓ Precise temperature and shaking control for reproducible results
- ✓ Robust construction for long-lasting performance
- ✓ User-friendly interface with easy operation
- ✓ Ideal for a wide range of laboratory applications

ADDRESS

62 Azad Nagar, Near Rampur Chowk,
Behind Khalsa Tent House,
Ambala Cantt, Haryana,
133001 India

CONTACT DETAILS

✉ Info@eselindia.com
✉ Sharma_electrical@yahoo.com
✉ asinternational024@gmail.com
☎ +91 9416183370
☎ +91 9416493069, +91 9306996454
👤 International Business
+91 7015448621

WEBSITE

🌐 www.eselinternational.org
www.esellab.com

also on
trade.gov.in