



For more
Information



Please Scan
the QR code

BHARAT BIKER 10W30 (AT)

Bharat Biker 10W30 Advance Technology oil crafted from Blend of Mineral base stock and high-Performance additives is specially designed keeping in view the high temperature operating conditions encountered in air cooled 4 strokes 2-wheeler engines unlike in the case of passenger car engines, which are water cooled. Further these oils possess special frictional properties required for smooth operation of wet clutches used in these vehicles. These oils provide outstanding oxidation and wear protection for extended oil & engine life.

Application:

- Latest generation high performance Motorcycles and Scooters.
- Suitable for earlier models of Motorcycles and Scooters.



Performance Benefits:

It provides enhanced protection against oxidation and, wear, thereby ensuring smoother performance, cleaner engine and longer engine & oil life. BHARAT BIKER 10W-30 is designed to tackle challenges like traffic, extreme climates, and low-quality fuel, which can cause engine deposits and performance issues. Its advanced formula cleans old deposits and prevents new ones, offering up to 40% better protection than industry standards. The additive also provides superior deposit protection, maintains viscosity against breakdown, extends engine life, and improves gas mileage.

- Superior deposit protection with unique technology
- Maximum viscosity against breakdown
- Helps extend engine life
- Ultra-low friction for improved gas mileage
- Outperformed industry standards in the Sequence VG sludge test

Recommendation:

Bharat Biker 20W40 (AT) 4 stroke bike engine oil can be use up to 125 CC engine bikes.

Typical Data Specifications:

SR. NO.	CHARACTERISTICS	TEST	UNIT	RANGE
1	SAE Rating	-	-	10W30
2	Performance Level	-	-	API SN
3	Appearance	VISUAL	-	C & B
4	Kinematic Viscosity @ 40°C cSt	ASTM D445	mm ² /s	75
5	Kinematic Viscosity @ 100°C cSt	ASTM D445	mm ² /s	11
6	Viscosity Index min.	ASTM D2270	none	140
7	Flash Point COC °C	ASTM D92	°C	>200°C
8	Pour Point °C max.	ASTM D97	°C	-33 (-36)°C
9	TBN min.	ASTM D2896	mgKOH/g	8

*The specifications are subject to variations/development/customization.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Available Packing Sizes: 800ml, 900ml, 1 ltr, 50 ltrs, 55 ltrs, 210 ltrs.

Health & Safety: based on available information, this product is not expected to produce any adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the internet. This product should not be used for purposes other than its intended use, if disposing of used product, take care to protect the environment.