



RS 400

Thyristorised welding rectifier



Robust & Reliable

RS 400 is a thyristorised welding power source designed to withstand tough working conditions with excellent welding output characteristics makes this preferred choice for outdoor and onsite usage.

- Easy arc striking and ripple free output reduce rework
- Suitable for use with Long Lead and cellulosic electrode
- Heavy duty performance with insulation class H
- Heavy duty under carriage with large wheel and handle - ease of machine movement

Visit esabindia.com for more information.

Industry

- Heavy Fabrication
- Construction & Projects
- Repair & Maintenance



Specification	
Mains Supply, V/Ph, Hz	415 ± 10% / 3, 50
Rated Input Current, A	27
Rated Input Power (Max) KVA	18
Output Current Range, A	10 – 400
Open Circuit Voltage, V	90
Efficiency, %	75
Enclosure Class	IP21
Insulation Class	H
Cooling	Forced Air
Dimensions, L x W x H, mm	825 x 695 x 1070
Weight, Kg	195

Ordering Information	
Description	Part number
RS 400	4610621400
Handicool HC600	2002001001
Heavy Duty Earth Clamp 600	2002002001
HFR Welding Cable Al 70 Sq mm	4600600191
Bench Oven, 45 Kgs	2002003005
Eco Arc II Helmet (83 X 108mm)	0700000986
Filter Lens - Shade 13, 83x108	0701416376
A20 Auto-Darkening Helmet	0700000720
Welding Hand Gloves (5 pair)	2001005011
Welding Apron (Large)	2001007001
Welding Sleeve	2001007002
Welding Leg Guard	2001007003

Note: RS 400 is delivered with remote.



www.esabindia.com

