



UNIVERSAL SALES AGENCY

HSN-3917
GST @ 18 %

Tele (079) 22161042 | 29621275
22161048

M. : 99252 31275
☎ : 98790 19875

E-mail (1) unipec.india@gmail.com
(2) universalgroup.help@gmail.com

Office : 696, Reid Road, O/s. Panchkva Gate, Opp. Hariom Market No.2, Nr. Railway Station, Kalupur, Ahmedabad-380002.

New Office Shed No.20-A, Sardar Patel Ind. Estate, Narol Circle To Vatva Turning, Nr. Over Bridge, Narol, Ahmedabad-382405.

DUPLON
STEEL WIRE HOSE

PRICE LIST

W.e.f. Dt. 01/01/2021

STEEL WIRE PVC HOSE (THUNDER HOSE)

(S.S. - Spring Steel Wire Reinforced)



Rate / mtr.

SIZE		Dimension		Wall Thickness (mm)	Working Pressure (kg/cm ²)	Standard Length (mtrs.)	Rates Per Mtr. (Rs.)
in (mm)	in (inch)	Inside (mm)	Outside (mm)				
12	(½")	12.7	18.7	3.0 ± 0.2 mm	7 kg/cm ²	50 x ₁ / 100 x ₁	62=00
15	(5/8")	15.8	22.8	3.5 ± 0.2 mm	6 kg/cm ²	50 x ₁ / 100 x ₁	88=00
20	(¾")	19.0	26.0	3.5 ± 0.2 mm	6 kg/cm ²	50 x ₁ / 100 x ₁	118=00
25	(1")	25.4	33.4	4.0 ± 0.2 mm	5 kg/cm ²	50 x ₁ / 100 x ₁	166=00
31	(1¼")	31.8	39.8	4.0 ± 0.2 mm	5 kg/cm ²	30 x ₁ / 50 x ₁	238=00
40	(1½")	38.1	47.1	4.5 ± 0.2 mm	5 kg/cm ²	30 x ₁ / 50 x ₁	292=00
50	(2")	50.8	60.8	5.0 ± 0.3 mm	5 kg/cm ²	30 x ₁ / 50 x ₁	414=00
65	(2½")	63.0	74.0	5.5 ± 0.2 mm	5 kg/cm ²	30 x ₁	488=00

DUTRON
Kanaflex

NON-TOXIC PVC HOSE (ANTI-STATIC HOSE)

(Copper Wire Reinforced)



SIZE		Dimension		Wall Thickness in (mm)	Working Pressure in (kg/cm ²)	Packing Length in (mtrs.)	Non-Toxic Hose Pipe	
in (mm)	in (inch)	Inside (mm)	Outside (mm)				(Transparent) [Clear] (Rs./mtr.)	(Copper Wire) [Antistatic] (Rs./mtr.)
25	1"	25.4	33.3	2.5 ± 0.2 mm	7 kg/cm ²	30 x ₁	126=00	230=00
30	1¼"	31.8	36.8	2.5 ± 0.2 mm	7 kg/cm ²	30 x ₁	170=00	258=00
38	1½"	38.0	43.3	2.7 ± 0.2 mm	6.5 kg/cm ²	30 x ₁	220=00	388=00
40	1½"	40.2	45.3	2.7 ± 0.2 mm	6.5 kg/cm ²	30 x ₁	-	388=00
50	2"	50.8	57.8	3.5 ± 0.2 mm	5 kg/cm ²	30 x ₁	352=00	628=00
60	2¼"	60.0	70.8	3.7 ± 0.2 mm	4 kg/cm ²	30 x ₁	454=00	684=00
65	2½"	63.5	72.0	4.2 ± 0.2 mm	4 kg/cm ²	30 x ₁	454=00	756=00
75	3"	76.2	85.0	4.5 ± 0.3 mm	3.5 kg/cm ²	30 x ₁	590=00	914=00
100	4"	101.2	112.2	5.5 ± 0.3 mm	3.5 kg/cm ²	30 x ₁	980=00	1,414=00

--> Suitable for, Milk, Dairy, Pharmaceuticals, Food & Beverages Applications.

--> Non-Toxic Material (Food-Grade). With FDA Approved TC.

--> Temperature Capacity : Max. Upto 70 Deg. C.



Note:

- * Pressure --> 1 Kg./cm² = 0.98 bar (14.22 psi)
- * Pressure --> 1 Kg./cm² = 735 mm of HG (Vacuum Pressure)
- * Pressure --> 1 Kg./cm² = 394 in H₂O (Vacuum Pressure)
- * Bursting Capacity = 3 x Working Pressure (Approx.) - 3 Times.

