



UNIVERSAL SALES AGENCY

HSN-3917 3210
+ GST @ 18 %

Tele (079) 29621275
22161042
22161048

M. : 99252 31275
93160 24277
99252 31039

E-mail (1) info@universalpipes.in
(2) account@universalpipes.in

New Office → Shed No.20-A, Sardar Patel Ind. Estate, Narol Circle To Vatva Turning, Nr. Over Bridge, Narol, Ahmeabad-382405.

DUPLON
STEEL WIRE HOSE



STEEL WIRE PVC HOSE (THUNDER HOSE)

(S.S. - Spring Steel Wire Reinforced)

PRICE LIST

Dt. 01-08-2022



SIZE		Dimension		Wall Thickness (mm)	Working Pressure (kg/cm ²)	Standard Length (mtrs.)	D-STEELTH- (012) (100)
in (mm)	in (inch)	Inside (mm)	Outside (mm)				(Rs.) - Per Mtr.
12	(½")	12.7	18.7	3.0 ± 0.2 mm	7 kg/cm ²	50 x ₁ / 100 x ₁	66=00
15	(5/8")	15.8	22.8	3.5 ± 0.2 mm	6 kg/cm ²	50 x ₁ / 100 x ₁	94=00
20 (19)	(¾")	19.0	26.0	3.5 ± 0.2 mm	6 kg/cm ²	50 x ₁ / 100 x ₁	126=00
25	(1")	25.4	33.4	4.0 ± 0.2 mm	5 kg/cm ²	50 x ₁ / 100 x ₁	178=00
30 (31)	(1¼")	31.8	39.8	4.0 ± 0.2 mm	5 kg/cm ²	30 x ₁ / 50 x ₁	255=00
40 (38)	(1½")	38.1	47.1	4.5 ± 0.2 mm	5 kg/cm ²	30 x ₁ / 50 x ₁	312=00
50 (51)	(2")	50.8	60.8	5.0 ± 0.3 mm	5 kg/cm ²	30 x ₁ / 50 x ₁	443=00
65 (63)	(2½")	63.0	74.0	5.5 ± 0.2 mm	5 kg/cm ²	30 x ₁	522=00

→ Suitable for, Milk, Dairy, Pharmaceuticals, Food & Beverages Applications.


→ Non-Toxic Material (Food-Grade). With FDA Approved TC.

DUTRON
Kanaflex



NON-TOXIC PVC HOSE (ANTI-STATIC HOSE)

(Copper Wire Reinforced)



SIZE		Dimension		Wall Thickness in (mm)	Working Pressure in (kg/cm ²)	Packing Length in (mtrs.)	Non-Toxic Hose Pipe	
in (mm)	in (inch)	Inside (mm)	Outside (mm)				(NT-Plain)	(NT-Copper Wire)
							D-NTPLAIN- (025) (030)	D-NTCOPER- (025) (030)
							[Clear]	[Antistatic]
							(Rs./mtr.)	(Rs./mtr.)
25	1"	25.4	33.3	2.5 ± 0.2 mm	7 kg/cm ²	30 x ₁	136=00	250=00
30 (31)	1¼"	31.8	36.8	2.5 ± 0.2 mm	7 kg/cm ²	30 x ₁	185=00	280=00
40 (38)	1½"	38.0	43.3	2.7 ± 0.2 mm	6.5 kg/cm ²	30 x ₁	240=00	423=00
40 (40)	1½"	40.2	45.3	2.7 ± 0.2 mm	6.5 kg/cm ²	30 x ₁	240=00	423=00
50 (51)	2"	50.8	57.8	3.5 ± 0.2 mm	5 kg/cm ²	30 x ₁	384=00	683=00
60	2¼"	60.0	70.8	3.7 ± 0.2 mm	4 kg/cm ²	30 x ₁	494=00	744=00
65 (63)	2½"	63.5	72.0	4.2 ± 0.2 mm	4 kg/cm ²	30 x ₁	494=00	824=00
75	3"	76.2	85.0	4.5 ± 0.3 mm	3.5 kg/cm ²	30 x ₁	642=00	994=00
100	4"	101.2	112.2	5.5 ± 0.3 mm	3.5 kg/cm ²	30 x ₁	1068=00	1539=00

→ Suitable for, Milk, Dairy, Pharmaceuticals, Food & Beverages Applications.

→ Non-Toxic Material (Food-Grade). With FDA Approved TC.



Note:

* Pressure --> 1 Kg./cm² = 0.98 bar (14.22 psi)

* Pressure --> 1 Kg./cm² = 735 mm of HG (Vacuum Pressure)

* Pressure --> 1 Kg./cm² = 394 in H₂O (Vacuum Pressure)

