



COMPANY PROFILE

ITIKAA ITECH PVT LTD, founded in 2014 and headquartered in Noida, specializes in the flat panel display terminal & LED bulb products.

The Group mainly consists of:
ITIKAA Itech Pvt. Ltd.
ITIKAA Commercial Display Technology.
ITIKAA Intelligent Technology.
ITIKAA Itech LED Lights.

ITIKAA has established a stable sales network, aftersales service centers and maintained good cooperative relationship with national famous top brand.

ITIKAA has enough partnership factories all over in India so as to offer quicker delivery and lower cost if necessary.


PRODUCT LIST

| 32" SM TG | 24" HD | 24" HD TG | 24" SM |
|-------------------|--------|-----------|--------|
| PREM 40" SM TG | 32" HD | 32" HD TG | 32" SM |
| TURE 43" SM 4K | 40" HD | 40" HD TG | 40" SM |
| COLL | 43" HD | 43" HD TG | 43" SM |
| 55" SM 4K | 50" HD | | |
| 65" SM 4K | 55" HD | | |





4K UHD LED TV with Mini LED BLU


- 1. Wide Color Gamut: Ultra-high color gamut coverage shows 1.07 billion level of rich color.
- 2. Pure Chroma: 4K UHD is a display with pure color.
- 3. Lasting Color: 4K UHD due to inorganic material characteristics does not fade with lasting 6W hours.














Smart TV Launcher AOSP Android









Anti-blue Light


adopts specially developed low-blue light LED chip, which can effectively filter about 90% shortwave blue light of 400-450nm that is harmful to human body.





OYouTube

See what the world is watching — from the hottest music videos to what's trending in gaming, entertain - ment, news, and more.






prime video

Amazon's comprehensive digital video service offers customers around the world a selection they won't find anywhere else, all available to watch on practically any device.








NETFLIX

Netflix is the world's leading subscription service for watching TV episodes and monies on your favorite











▲ SIGNATURE COLLECTION

| Size | 50″ | 55″ | 65″ |
|---------------------------|-----------------|----------------|------------------|
| Resolution | 4K UHD | 4K UHD | 4K UHD |
| Dimension (without Stand) | 970.2 x 563.2 x | 1124.8 x 650.2 | 1457.5 x 837.3 x |



prime video





Stand base





Optional color:









Streamlined Design

Precious metal texture has greatly improv-ed the expressiveness of the product.




Full HD picture quality, discover the beauty of detail, enjoy every amazing pixels experience.



Strong Compatibility

Highlighting the product's inspiration, technology and brand differentiation.



Lean production improves product quality and accelerat 17



Optimized Cost

Optimized Cost benefits product matrix and higher cost performance.



Customizable Logo Base Trim and Color

From succinctness to minimalism to gorgeous ness, mechanical beauty is fully flared.







| FEATURES | | | | | | | |
|---------------------------|-----------|-----------|-----------|-----------|-----------|----------|--|
| | 32" SM TG | 40" SM TG | 43" SM 4K | 50" SM 4K | 55" SM 4K | 65" SM4K | |
| SCREEN SIZE | 80cm | 99CM | 109CM | 127CM | 140CM | 165CM | |
| Toughned Glass/FHD/4K/UHD | TG, FHD | TG,FHD | 4K FHD | 4K UHD | 4K UHD | 4K UHD | |
| USB PORT | 2 | 2 | 2 | 2 | 2 | 2 | |
| HDMI PORT | 2 | 2 | 2 | 2 | 2 | 2 | |
| AV PORT | 1 | 2 | 2 | 2 | 2 | 2 | |
| VGA PORT | 1 | 1 | 1 | 1 | 1 | 1 | |
| EARPHONE PORT | 1 | 1 | 1 | 1 | 1 | 1 | |
| RF PORT | 1 | 1 | 1 | 1 | 1 | 1 | |
| SD CARD SLOT | | - | 1 | 1 | 1 | 1 | |
| Andriod version | 8 | 8 | 8 | 8 | 8 | 8 | |
| WiFi Inbuilt | YES | YES | YES | YES | YES | YES | |
| RAM | 1GB | 1GB | 1GB | 1GB | 1GB | 1GB | |
| ROM | 8GB | 8GB | 8GB | 8GB | 8GB | 8GB | |
| WARRANT | 1 Year | 1 Year | |





Remote Control

Appearances are designed according to customers' requirements.






RC-XX-1S













▲ ITIKAA FACTORY, NOIDA

12,000 SQFT ITIKAA R&D BASE

26,000 SQFT ITIKAA PRODUCTION BASE

600 EMPLOYE 182500 ANNUAL PRODUCTION











| LED BULB | | | | | | |
|----------|--------------|-------|------|-----|--|--|
| SR. NO | PRODUCT CODE | LUMEN | WATT | MRP | | |
| | II40B | 500 | 5 | 110 | | |
| 2 | II42B | 700 | 7 | 145 | | |
| 3 | II44B | 900 | 9 | 165 | | |
| 4 | II70B | 1200 | 12 | 200 | | |
| 5 | II85B | 1500 | 15 | 250 | | |
| 6 | II120B | 1800 | 18 | 290 | | |
| 7 | II200B | 2000 | 25 | 400 | | |
| 8 | II350B | 4000 | 40 | 780 | | |

SPECIFICATION

Input Voltage -90-300 V-AC, LED - Philips/Osram/Seoul, Color - Pure White/Warm white, C.C.T 5500- 6500K(CW), Efficiency >85%, Life spam: >50000 hours, Power Factor >0.95, T.H.D <10%, Surge Protection 4KV



| TUBE LIGHT | | | | | | | |
|------------------------------------|---------|-----|---|-----|--|--|--|
| SR. NO PRODUCT CODE LUMEN WATT MRP | | | | | | | |
| 1 | II85TL | 500 | 5 | 250 | | | |
| 2 | II120TL | 700 | 7 | 350 | | | |
| SPECIFICATION | | | | | | | |

Input Voltage -90-300 V-AC, LED - Philips/Osram/Seoul, Color - Pure White/Warm white, C.C.T 5500-6500K(CW), Efficiency >85%, Life spam: >50000 hours, Power Factor >0.95, T.H.D <10%, Surge Protection 4KV



| AC-DC BULB | | | | | | | |
|------------------------------------|---------|--|---|-----|--|--|--|
| SR. NO PRODUCT CODE LUMEN WATT MRP | | | | | | | |
| 1 | II190RL | | 9 | 650 | | | |
| SPECIFICATION | | | | | | | |
| | | | | | | | |

1000(AC) 300 (DC) Power backup Up to 4 hrs







STREET LIGHT

| SR. NO | PRODUCT CODE | LUMEN | WATT | MRP |
|--------|--------------|-------|------|-------|
| 1 | II400ST | 1500 | 15 | 2,100 |
| 2 | II410ST | 2000 | 20 | 2,268 |
| 3 | II500ST | 2400 | 24 | 2,940 |
| 4 | II510ST | 3000 | 30 | 3,108 |
| 5 | II600ST | 3600 | 36 | 3,500 |
| 6 | II840ST | 4500 | 45 | 4,900 |
| 7 | II870ST | 6000 | 60 | 5,068 |
| 8 | II1350ST | 8000 | 80 | 7,140 |
| 9 | II1400ST | 10000 | 100 | 7,980 |

SPECIFICATION

Input Voltage -90-300 V-AC, LED - Philips/Osram/Seoul, Color - Pure White/Warm white, C.C.T 5500-6500K(CW), Efficiency >85%, Life spam: >50000 hours, Power Factor >0.95, T.H.D <10%, Surge Protection 4KV



FLOOD LIGHT

| SR. NO | PRODUCT CODE | LUMEN | WATT | MRP | |
|--------|--------------|-------|------|-------|--|
| | II575FL | 3000 | 30 | 2,940 | |
| 2 | II750FL | 5000 | 50 | 3,920 | |
| 3 | II1150FL | 10000 | 100 | 5,740 | |
| 4 | II1850FL | 15000 | 150 | 9,240 | |

SPECIFICATION

Input Voltage -90-300 V-AC, LED - Philips/Osram/Seoul, Color - Pure White/Warm white, C.C.T 5500-6500K(CW), Efficiency >85%, Life spam: >50000 hours, Power Factor >0.95, T.H.D <10%, Surge Protection 4KV









| PANEL LIGHT | | | | | | |
|-------------|-------------|-------|------|------|--|--|
| SR. NO | PRODUT CODE | LUMEN | WATT | MRP | | |
| | II90PL | 300 | 3 | 420 | | |
| 2 | II125PL | 600 | 6 | 616 | | |
| 3 | II170PL | 1200 | 12 | 868 | | |
| 4 | II230PL | 1800 | 18 | 1176 | | |

SPECIFICATION

Input Voltage -90-300 V-AC, LED - Philips/Osram/Seoul, Color - Pure White/Warm white, C.C.T 5500-6500K(CW), Efficiency >85%, Life spam: >50000 hours, Power Factor >0.95, T.H.D <10%, Surge Protection 4KV



| HIGH BAY LIGHT | | | | | | | |
|----------------|-------------|-------|------|------|--|--|--|
| SR. NO | PRODUT CODE | LUMEN | WATT | MRP | | | |
| | II1500HB | 5500 | 50 | 3000 | | | |
| 2 | II2500HB | 11000 | 100 | 4500 | | | |
| 3 | II3500HB | 16500 | 150 | 6500 | | | |
| 4 | II50000HB | 22000 | 200 | 8500 | | | |
| SPECIFICATION | | | | | | | |

Input Voltage -90-300 V-AC, Color - Pure White/Warm white, Life spam: >50000