


# TECHNICAL DATA SHEET

|                |                     |  |
|----------------|---------------------|--|
| <b>PRODUCT</b> | <b>MASKING TAPE</b> |  <p>F-1, Sarda Chamber-1, Central Market,<br/>Prashant Vihar (Rohini), Delhi -<br/>110085 (INDIA)<br/>Tel.: +91 11 27555991-99<br/>Fax: +91 11 27555992<br/>E-mail: <a href="mailto:hmsales@chemlineglobal.com">hmsales@chemlineglobal.com</a><br/><a href="mailto:sales3@chemlineglobal.com">sales3@chemlineglobal.com</a><br/><a href="mailto:exports@chemlineglobal.com">exports@chemlineglobal.com</a><br/><a href="mailto:info@chemlineglobal.com">info@chemlineglobal.com</a></p> |
| <b>BRAND</b>   | <b>QUIKTACK</b>     |  |
| <b>GRADES</b>  | <b>MT-804</b>       |  |

\* Last updated on Dt.15.09.2020

## AREA OF APPLICATION

**QUIKTACK MT-804** Masking Tape is manufactured with smooth crepe paper coated with pressure-sensitive adhesive. It is used whereas clean removal is desired like- Interior paint masking, spray painting, furniture making, Automotive application, silk screening, mail rooms, marble Manufacturing (man-made), golf club shaft (build-up), carpet pad / pad splicing, freezer tape, and light bundling, packaging etc.

## TECHNICAL CHARACTERISTICS

| PARAMETERS                                  | MT-804                       |
|---|------------------------------|
| <b>Appearance</b>                           | Off White                    |
| <b>Total Micron (Paper + Adhesive)</b>      | 110 ± 5                      |
| <b>Total GSM</b>                            | 95 ± 5                       |
| <b>Peel Strength (N/cm)</b>                 | 2.5 ± 10%                    |
| <b>Shear Strength (hrs)</b>                 | 8 - 10 hrs.                  |
| <b>Tensile Strength (kg/cm<sup>2</sup>)</b> | 250 kg/cm <sup>2</sup>       |
| <b>% Elongation (at break)</b>              | 10 %                         |
| <b>Service Temperature range</b>            | +10 ~ +90°C (for 30 minutes) |



**Storage condition & Shelf life:** - One Years when stored at 25 - 30°C/ 50 - 60 % RH.

**Available Size:** - size and length is available as per customer requirement

|                      |                     |
|----------------------|---------------------|
| 24 mm x 20 mtr Long, | 48 mm x 20 mtr long |
| 24 mm x 50 mtr long, | 48 mm x 50 mtr long |

Disclaimer: The above data/information and suggestions contained in this literature are based on our study and experience. We recommend that before using our products in full scale production, the customer should make his own tests to determine the suitability of the products. Our field staff and technical personnel shall be happy to assist you in conducting tests. **The specification given in the document is subject to be change due to continuous modification/ up gradation in the product.**