



SIMATIC S7-200 SMART CPU CR20s, COMPACT CPU, AC/DC/RELAY;
ONBOARD I/O: 12 DI 24V DC; 8 DO RELAY 2A; POWER SUPPLY: AC, 85 - 264
V AC AT 47 - 63 HZ, PROGRAM/DATA MEMORY: 20 KB

General information	
Product type designation	CPU CR20 AC/DC/relay
Engineering with	
• Programming package	STEP 7 Micro/WIN SMART
Installation type/mounting	
Rail mounting	Yes; Standard - DIN rail
Supply voltage	
Rated value (AC)	230 V; 230 V AC (L1, N)
• 120 V AC	Yes; 85 to 132 V AC
• 230 V AC	Yes; 170 to 264 V AC
permissible range, lower limit (AC)	85 V
permissible range, upper limit (AC)	264 V
Reverse polarity protection	No
Line frequency	
• permissible range, lower limit	47 Hz
• permissible range, upper limit	63 Hz
Load voltage L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	5 V
• permissible range, upper limit (DC)	250 V
Input current	
Current consumption (rated value)	60 mA; At 220 V AC
Current consumption, max.	80 mA; At 220 V AC
Inrush current, max.	16.3 A; at 264 V
Power loss	
Power loss, max.	6 W
Memory	
Type of memory	DDR
Flash	Yes
RAM	Yes
Micro Memory Card	No
CPU processing times	
for bit operations, typ.	150 ns; / instruction
for word operations, typ.	1.2 µs; / instruction
for floating point arithmetic, typ.	3.6 µs; / instruction
Hardware configuration	
Integrated power supply	No
Time of day	
Clock	
• Type	Software clock

• Hardware clock (real-time)	No
Digital inputs	
Number of digital inputs	12; Integrated
• of which inputs usable for technological functions	4; HSC: 4 @ 100 kHz single phase, 2 @ 50 kHz A/B phase
Source/sink input	Yes
Input voltage	
• Type of input voltage	DC
• Rated value (DC)	24 V; DC at 4 mA nominal
• for signal "0"	< 5 V DC
• for signal "1"	+15 to +30 V
Input current	
• for signal "0", max. (permissible quiescent current)	1 mA
• for signal "1", typ.	4 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; 0.2 µs, 0.4 µs, 0.8 µs, 1.6 µs, 3.2 µs, 6.4 µs and 12.8 µs, selectable in 4 groups
— at "0" to "1", min.	0.2 µs
— at "0" to "1", max.	12.8 µs
for interrupt inputs	
— parameterizable	Yes
Cable length	
• shielded, max.	500 m; Standard input: 500 m, high-speed counters: 50 m
• unshielded, max.	300 m
Digital outputs	
Number of digital outputs	8; Relays
Switching capacity of the outputs	
• with resistive load, max.	2 A
• on lamp load, max.	30 W; 30 W with DC, 200 W with AC
Output delay with resistive load	
• "0" to "1", max.	10 ms; max.
• "1" to "0", max.	10 ms; max.
Switching frequency	
• of the pulse outputs, with resistive load, max.	1 Hz
Relay outputs	
• Number of relay outputs	8
• Number of operating cycles, max.	10 000 000; mechanically 10 million, at rated load voltage 100 000
Cable length	
• shielded, max.	500 m
• unshielded, max.	300 m
Interfaces	
Number of industrial Ethernet interfaces	0
Number of RS 485 interfaces	1
Optical interface	No
1. Interface	
Interface type	RS 485 (max. 187.5 kbps)
Isolated	Yes; 500 V AC or 707 V DC
Interface types	
• RS 485	Yes
• Design of the connection	9-pin sub D socket
Protocols	
Supports protocol for PROFINET IO	No
PROFIBUS	No
Protocols (Ethernet)	
• TCP/IP	No
EMC	
Interference immunity against discharge of static electricity	
• Interference immunity against discharge of static electricity acc. to IEC 61000-4-2	Yes
— Test voltage at air discharge	8 kV
— Test voltage at contact discharge	4 kV

Interference immunity against high-frequency electromagnetic fields	
- Interference immunity against high-frequency radiation acc. to IEC 61000-4-3 - Frequency range of the RF radiation	Yes; 10 V/m, 80 to 1 000 MHz (to IEC 61000-4-3); 10 V/m, 900 MHz, 1.89 GHz, 50% ED (to IEC 61000-4-3) 10 V/m for 80 MHz ~ 1 GHz, 3 V/m for 1.4 GHz ~ 2 GHz, 3 V/m for 87 MHz ~ 108 MHz, 174 MHz ~ 230 MHz, 470 MHz ~ 790 MHz, 1.4 GHz ~ 2 GHz, 1 V/m for 2 GHz ~ 2.7 GHz
Interference immunity to cable-borne interference	
- Interference immunity on supply lines acc. to IEC 61000-4-4 - Interference immunity on signal cables acc. to IEC 61000-4-4	Yes; ±2 kV acc. to IEC 61000-4-4, burst; surge measurements with additional protective elements Yes; ±2 kV acc. to IEC 61000-4-4, Burst
Interference immunity against voltage surge	
- Interference immunity on supply lines acc. to IEC 61000-4-5 - asymmetric interference - Test voltage on supply cables - Test voltage on signal cables >30m	Yes; ±1 kV (acc. to IEC 61000-4-5; 1995; surge symm.), ±2 kV (acc. to IEC 61000-4-5; 1995; surge asymm.), no external protective circuit required 2 kV 2 kV
Interference immunity against conducted variable disturbance induced by high-frequency fields	
Interference immunity against high frequency current feed acc. to IEC 61000-4-6	Yes; 10 V, 150 kHz to 80 MHz (to IEC 61000-4-6)
Emission of radio interference acc. to EN 55 011	
Limit class A, for use in industrial areas	Yes; Emission of radio interference acc. to EN 61000-6-4 +A1 for use in industrial environments
Emission of conducted and non-conducted interference	
Interference emission via line/AC current cables	EN 61000-6-4, interference emission: Intended for use in industrial areas.
Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Free fall	
Fall height, max.	0.5 m; five times, in product package
Ambient temperature during operation	
- min. - max. - horizontal installation, min. - horizontal installation, max. - vertical installation, min. - vertical installation, max.	0 °C 55 °C 0 °C 55 °C 0 °C 45 °C
Ambient temperature during storage/transportation	
- min. - max.	-40 °C 70 °C
Air pressure acc. to IEC 60068-2-13	
- Storage/transport, min. - Storage/transport, max.	660 hPa 1 080 hPa
Altitude during operation relating to sea level	
- Installation altitude, min. - Installation altitude, max.	-1 000 m 2 000 m
Relative humidity	
Operation at 25 °C without condensation, max.	95 %
configuration / header	
configuration / programming / header	
Programming language	
- LAD - FBD - STL	Yes Yes Yes
Dimensions	
Width	90 mm
Height	100 mm
Depth	81 mm
Weights	
Weight, approx.	365 g; approx.

Classifications

	Version	Classification
eClass	14	27-24-22-07
eClass	12	27-24-22-07
eClass	9.1	27-24-22-07
eClass	9	27-24-22-07
eClass	8	27-24-22-07
eClass	7.1	27-24-22-07
eClass	6	27-24-22-07
ETIM	9	EC000236
ETIM	8	EC000236
ETIM	7	EC000236
IDEA	4	3565
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval



last modified:

3/12/2024