

SIMATIC S7-200 SMART, CPU ST40, CPU, DC/DC/DC, onboard I/O: 24 DI 24 V DC; 16 DO 24 V DC; power supply: DC 20.4 - 28.8 V DC, program/data memory 40 KB web server support

General information	
Product type designation	CPU ST40 DC/DC/DC
Engineering with	
• Programming package	STEP 7 Micro/WIN SMART
Installation type/mounting	
Rail mounting	Yes; Standard - DIN rail
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption, max.	680 mA; 24 V DC
Inrush current, max.	11.7 A; at 28.8 V
Output current	
Current output, max.	300 mA; 24 V DC Sensor Power
for backplane bus (5 V DC), max.	1.4 A; max. 5 V DC for EM bus
Power loss	
Power loss, max.	18 W
Memory	
Type of memory	DDR
Flash	Yes
RAM	Yes
Memory available for user data	16 kbyte
Memory size	24 kbyte; Program memory
Micro Memory Card	Yes; microSDHC Card (optional)
Backup	
• present	Yes; Maintenance free, RTC requires 7 days.
CPU processing times	
for bit operations, typ.	150 ns; / instruction
for word operations, typ.	1.2 µs; / instruction
for floating point arithmetic, typ.	3.6 µs; / instruction
Address area	
I/O address area	
• Inputs	144 byte; 256 bit of digital inputs & 56 words of analog inputs
• Outputs	144 byte; 256 bit of digital outputs & 56 words of analog outputs
Time of day	
Clock	
• Type	Hardware clock, no battery backup
• Hardware clock (real-time)	Yes
• Backup time	7 d
• Deviation per day, max.	120 s; within 120s/month at 25 °C
Digital inputs	
Number of digital inputs	24; Integrated
• of which inputs usable for technological functions	6; HSC (High Speed Counting)
Source/sink input	Yes
Number of simultaneously controllable inputs	
all mounting positions	
— up to 40 °C, max.	24
Input voltage	
• Type of input voltage	DC

- Rated value (DC) - for signal "0" - for signal "1"	24 V I0.0 to I0.3 < 1 V DC; I0.4 to I2.7 < 5 V DC I0.0 to I0.3 > 4V; I0.4 to I2.7 > 15V
Input current	
- for signal "0", max. (permissible quiescent current) - for signal "1", typ.	1 mA 4 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; 0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in groups of four
— at "0" to "1", min.	0.2 ms
— at "0" to "1", max.	12.8 ms
for interrupt inputs	
— parameterizable	Yes
for technological functions	
— parameterizable	Yes; 6 Single phase: 4 HSCs at 200 kHz; 2 HSCs at 30 kHz 4 A/B phase: 2 HSCs at 100 kHz; 2 HSCs at 20 kHz
Cable length	
- shielded, max. - unshielded, max.	500 m; 50 m for technological functions 300 m; for technological functions: No
Digital outputs	
Number of digital outputs	16; Transistor
of which high-speed outputs	3; 100 kHz Pulse Train Output
Switching capacity of the outputs	
- with resistive load, max. - on lamp load, max.	0.5 A 5 W
Output voltage	
for signal "1", min.	20 V DC
Output current	
- for signal "1" rated value - for signal "0" residual current, max.	0.5 A 10 µA
Output delay with resistive load	
"0" to "1", max. "1" to "0", max.	3 µs; of the standard outputs, max. 3 µs; of the pulse outputs, max. (Q a.0 to Q a.3) 1 µs 200 µs; of the standard outputs, max. 200 µs; of the pulse outputs, max. (Q a.0 to Q a.3) 50 µs
Switching frequency	
of the pulse outputs, with resistive load, max.	100 kHz
Relay outputs	
Number of relay outputs	0
Cable length	
- shielded, max. - unshielded, max.	500 m 150 m
Interfaces	
Number of industrial Ethernet interfaces	1
Number of RS 485 interfaces	1
1. Interface	
Interface type	PROFINET
Isolated	Yes; Transformer isolated, 1,500V AC
automatic detection of transmission rate	Yes; 10/100 Mbit/s
Autonegotiation	Yes
Autocrossing	Yes
Interface types	
RJ 45 (Ethernet)	Yes
Protocols	
- PROFINET IO Controller - PROFINET IO Device	Yes; Since V2.4 Yes; I-Device since V2.5
PROFINET IO Controller	
Transmission rate, max.	100 Mbit/s
Services	
- Number of connectable IO Devices, max. - Updating time	8 4 ms; The minimum value of the update time also depends on the

		communication component set for PROFINET IO, on the number of IO devices and the quantity of configured user data.
Address area		
— Inputs, max.		128 byte; Per device
— Outputs, max.		128 byte; Per device
2. Interface		
Interface type		RS 485 (max. 187.5 kbps)
Interface types		
• RS 485		Yes
PROFIBUS DP master		
Services		
— S7 communication		Yes
Protocols		
Supports protocol for PROFINET IO		Yes; RT Controller (since FW V2.4) & I-Device (since FW V2.5)
PROFIBUS		Yes; Via CM DP module
Protocols (Ethernet)		
• TCP/IP		Yes
communication functions / header		
S7 communication		
• supported		Yes
• as server		Yes
• as client		Yes
Test commissioning functions		
Status/control		
• Status/control variable		Yes
Forcing		
• Forcing		Yes
Integrated Functions		
PID controller		Yes; PID closed-loop control function: Continuous controller outputs, binary controller outputs, automatic/manual mode, max. 8 loops
Number of pulse outputs		3
Potential separation		
Potential separation digital inputs		
• between the channels, in groups of		1
Potential separation digital outputs		
• between the channels		No
• between the channels, in groups of		2
EMC		
Interference immunity against discharge of static electricity		
• Interference immunity against discharge of static electricity acc. to IEC 61000-4-2		Yes
— Test voltage at air discharge		8 kV
— Test voltage at contact discharge		4 kV
Interference immunity against high-frequency electromagnetic fields		
• Interference immunity against high-frequency radiation acc. to IEC 61000-4-3		Yes; 10 V/m, 80 to 1 000 MHz (to IEC 61000-4-3); 10 V/m, 900 MHz, 1.89 GHz, 50% ED (to IEC 61000-4-3)
Interference immunity to cable-borne interference		
• Interference immunity on supply lines acc. to IEC 61000-4-4		Yes; 2 kV acc. to IEC 61000-4-4, burst
• Interference immunity on signal cables acc. to IEC 61000-4-4		Yes; ±2 kV acc. to IEC 61000-4-4, Burst
Interference immunity against conducted variable disturbance induced by high-frequency fields		
• Interference immunity against high frequency current feed acc. to IEC 61000-4-6		Yes; 10 V, 150 kHz to 80 MHz (to IEC 61000-4-6)
Emission of radio interference acc. to EN 55 011		
• Limit class A, for use in industrial areas		Yes; EN 61000-6-4, interference emission: Intended for use in industrial areas.
Emission of conducted and non-conducted interference		
• Interference emission via line/AC current cables		EN 61000-6-4, interference emission: Intended for use in industrial areas.
Standards, approvals, certificates		
CE mark		Yes
Ambient conditions		
Free fall		

• Fall height, max.	0.3 m; five times, in product package		
Ambient temperature during operation			
• min.	-20 °C		
• max.	60 °C		
• horizontal installation, min.	-20 °C		
• horizontal installation, max.	60 °C		
• vertical installation, min.	-20 °C		
• vertical installation, max.	50 °C		
Ambient temperature during storage/transportation			
• min.	-40 °C		
• max.	70 °C		
Air pressure acc. to IEC 60068-2-13			
• Storage/transport, min.	660 hPa		
• Storage/transport, max.	1 080 hPa		
Altitude during operation relating to sea level			
• Installation altitude, min.	-1 000 m		
• Installation altitude, max.	2 000 m		
Relative humidity			
• Operation at 25 °C without condensation, max.	95 %		
configuration / header			
configuration / programming / header			
Programming language			
— LAD	Yes		
— FBD	Yes		
— STL	Yes		
Dimensions			
Width	125 mm		
Height	100 mm		
Depth	81 mm		
Weights			
Weight, approx.	410.3 g		
Classifications			
		Version	Classification
	eClass	14	27-24-22-07
	eClass	12	27-24-22-07
	eClass	9.1	27-24-22-07
	eClass	9	27-24-22-07
	eClass	8	27-24-22-07
	eClass	7.1	27-24-22-07
	eClass	6	27-24-22-07
	ETIM	9	EC000236
	ETIM	8	EC000236
	ETIM	7	EC000236
	IDEA	4	3565
	UNSPSC	15	32-15-17-05
Approvals / Certificates			
General Product Approval			



last modified:

12/8/2024