

SIMATIC S7-200 SMART, analog I/O SM AM06, 2AI/1AO, 0...10V,0...5V, 0/4...20mA, +/-5 V, +/-2.5 V, 12 bit resolution or 4...20 mA, +/-10 V, 11 bit resolution

General information	
Product type designation	SM AM03, AI 2x12 bit, AQ 1x11 bit
Power loss	
Power loss, typ.	1.1 W
Analog inputs	
Number of analog inputs	2
Input ranges	
• Voltage	Yes
• Current	Yes
• Thermocouple	No
• Resistance thermometer	No
• Resistance	No
Analog outputs	
Number of analog outputs	1
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	12 bit
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	11 bit
Dimensions	
Width	45 mm
Height	100 mm
Depth	81 mm
Weights	
Weight, approx.	172 g
Classifications	

	Version	Classification
eClass	14	27-24-22-01
eClass	12	27-24-22-01
eClass	9.1	27-24-22-01
eClass	9	27-24-22-01
eClass	8	27-24-22-01
eClass	7.1	27-24-22-01
eClass	6	27-24-22-01
ETIM	9	EC001420
ETIM	8	EC001420
ETIM	7	EC001420
IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates	
General Product Approval	



