

SIMATIC S7-200 SMART, Communication module CM 01, RS485, 9-pole D-sub (pin), supports Freeport

General information			
Product type designation		CM01 RS 485	
CiR - Configuration in RUN			
Reparameterization possible in RUN		No	
Input current			
from backplane bus 5 V DC, typ.		50 mA	
Power loss			
Power loss, typ.		0.5 W	
Interfaces			
Number of industrial Ethernet interfaces		0	
Number of RS 485 interfaces		1	
Protocols			
Supports protocol for PROFINET IO		No	
PROFIBUS		No	
Protocols (Ethernet)			
• TCP/IP		No	
Degree and class of protection			
IP degree of protection		IP20	
Standards, approvals, certificates			
CE mark		Yes	
Dimensions			
Width		35 mm	
Height		52.2 mm	
Depth		16 mm	
Weights			
Weight, approx.		18.2 g	
Classifications			
		Version	Classification
	eClass	14	27-24-22-08
	eClass	12	27-24-22-08
	eClass	9.1	27-24-22-08
	eClass	9	27-24-22-08
	eClass	8	27-24-22-08
	eClass	7.1	27-24-22-08
	eClass	6	27-24-22-08
	ETIM	9	EC001423
	ETIM	8	EC001423
	ETIM	7	EC001423
	IDEA	4	3564
	UNSPSC	15	32-15-17-05
Approvals / Certificates			
General Product Approval			



