



SIMATIC bus adapter: BA LC/RJ45, media converter glass FOC/CU 1x LC FO connection and 1x RJ45 connection

General information			
Product type designation	BA LC/RJ45		
HW functional status	from FS04		
Interfaces			
Number of PROFINET interfaces	1; 2 ports (switch) LC / RJ45		
Supports protocol for PROFINET IO			
• Number of RJ45 ports	1		
• Number of LC ports	1; Wavelength of 1 270 ... 1 380 nm, corresponds to 100BASE-FX		
Cable length			
— Cu conductors	100 m		
— Multimode graded-index fiber 50/125 µm	3 km		
— Multimode graded-index fiber 62.5/125 µm	3 km		
Ambient conditions			
Ambient temperature during operation			
• horizontal installation, min.	-30 °C		
• horizontal installation, max.	60 °C		
• vertical installation, min.	-30 °C		
• vertical installation, max.	50 °C		
Altitude during operation relating to sea level			
• Installation altitude above sea level, max.	5 000 m; restrictions for installation altitudes > 2 000 m, see ET 200SP system manual		
Dimensions			
Width	20 mm		
Height	69.5 mm		
Depth	59 mm		
Weights			
Weight, approx.	32 g		
Classifications			
		Version	Classification
	eClass	14	27-24-26-92
	eClass	12	27-24-26-92
	eClass	9.1	27-24-26-92
	eClass	9	27-24-26-92
	eClass	8	27-24-26-92
	eClass	7.1	27-24-26-92
	eClass	6	27-24-26-92
	ETIM	9	EC002584
ETIM	8	EC002584	

ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03

Approvals / Certificates

General Product Approval



[Manufacturer Declaration](#)



[KC](#)



For use in hazardous locations



[CCC-Ex](#)

[FM](#)



[Miscellaneous](#)

Marine / Shipping



[NK / Nippon Kaiji Kyokai](#)



Marine / Shipping



[CCS \(China Classification Society\)](#)



last modified: 5/22/2024