

SIMATIC S7-1500, CM PTP RS232 HF communications module for serial connection RS-232, freeport, 3964(R), USS, Modbus RTU master, device, 115200 bit/s, 9-pin D-sub plug

General information	
Product type designation	CM PtP RS 232 HF
Product function	
- I&M data - Fast startup	Yes; I&M 0 Yes
Engineering with	
- STEP 7 TIA Portal configurable/integrated from version - STEP 7 configurable/integrated from version - PROFIBUS from GSD version/GSD revision - PROFINET from GSD version/GSD revision	V18 with HSP 0367 / V19; with older TIA Portal versions configurable as 6ES7541-1AD00-0AA0 V5.5 SP2 with GSD file - / - GSDML V2.42
Installation type/mounting	
Rail mounting	Yes; S7-1500 mounting rail
Supply voltage	
Design of the power supply	system power supply
Input current	
Current consumption (rated value)	50 mA; From the backplane bus
Power	
Power available from the backplane bus	0.75 W
Power loss	
Power loss, typ.	0.6 W
Address area	
Address space per module	
- Inputs - Outputs	8 byte; performance mode: 32 byte 0 byte; performance mode: 32 byte
Interface types	
RS 232	
- Transmission rate, max. - Cable length, max. - RS 232 auxiliary signals	115.2 kbit/s 15 m RTS, CTS, DTR, DSR, RI, DCD
Protocols	
Integrated protocols	
Freeport	
- Telegram length, max. - Bits per character - Number of stop bits - Parity	4 kbyte 7 or 8 1 or 2 bit None, even, odd, always 1, always 0, any
3964 (R)	
- Telegram length, max. - Bits per character - Number of stop bits - Parity	4 kbyte 7 or 8 1 or 2 bit None, even, odd, always 1, always 0, any
Modbus RTU master	
- Address area - max. number of devices	1 to 247, extended 1 to 65535 1
protocols / Modbus RTU device / header	
Address area	1 to 247, extended 1 to 65535
Telegram buffer	
- Buffer memory for telegrams - Number of telegrams which can be buffered	8 kbyte 255

Interrupts/diagnostics/status information			
Diagnostics function	Yes		
Alarms			
Diagnostic alarm	Yes		
Hardware interrupt	No		
Diagnoses			
Wire-break	Yes		
Diagnostics indication LED			
RUN LED	Yes; green LED		
ERROR LED	Yes; red LED		
Receive RxD	Yes; Yellow LED		
Transmit TxD	Yes; Yellow LED		
Potential separation			
between backplane bus and interface	Yes		
Isolation			
Isolation tested with	707 V DC (type test)		
product functions / security / header			
signed firmware update	Yes		
Ambient conditions			
Ambient temperature during operation			
horizontal installation, min.	-30 °C		
horizontal installation, max.	60 °C		
vertical installation, min.	-30 °C		
vertical installation, max.	40 °C		
Altitude during operation relating to sea level			
Installation altitude above sea level, max.	5 000 m; restrictions for installation altitudes > 2 000 m, see ET 200MP system manual		
Decentralized operation			
to SIMATIC S7-300	Yes		
to SIMATIC S7-400	Yes		
to SIMATIC S7-1500	Yes		
to standard PROFINET controller	Yes		
Dimensions			
Width	35 mm		
Height	147 mm		
Depth	127 mm		
Weights			
Weight, approx.	0.22 kg		
Classifications			
		Version	Classification
	eClass	14	27-24-22-08
	eClass	12	27-24-22-08
	eClass	9.1	27-24-22-08
	eClass	9	27-24-22-08
	eClass	8	27-24-22-08
	eClass	7.1	27-24-22-08
	eClass	6	27-24-22-08
	ETIM	9	EC001423
	ETIM	8	EC001423
	ETIM	7	EC001423
Approvals / Certificates			
General Product Approval			EMV

[Manufacturer Declaration](#)



[KC](#)

For use in hazardous locations



[FM](#)

[CCC-Ex](#)



[Type Examination Certificate](#)



For use in hazardous locations	Marine / Shipping
--------------------------------	-------------------

[Miscellaneous](#)



[NK / Nippon Kaiji Kyokai](#)

Marine / Shipping



[CCS \(China Classification Society\)](#)



last modified:

11/7/2024 