



SIMATIC S7-400, rack aluminum UR2, central and distributed with 9 slots, 2 redundant PS can be plugged in

General information			
Product type designation		UR2	
Hardware configuration			
Rack			
• Communication bus		Yes	
• P bus		Yes	
Slots			
• Number of slots		9	
Standards, approvals, certificates			
CE mark		Yes	
UKCA mark		Yes	
UL approval		Yes	
FM approval		Yes	
RCM (formerly C-TICK)		Yes	
KC approval		Yes	
EAC (formerly Gost-R)		Yes	
CCC		Yes	
Ambient conditions			
Ambient temperature during operation			
• min.		0 °C	
• max.		60 °C	
Ambient temperature during storage/transportation			
• min.		0 °C	
• max.		70 °C	
Mechanics/material			
rack profile material		aluminum	
Dimensions			
Width		257.5 mm	
Height		290 mm	
Depth		27.5 mm	
Weights			
Weight, approx.		1.5 kg	
Classifications			
		Version	Classification
	eClass	14	27-24-22-03
	eClass	12	27-24-22-03
	eClass	9.1	27-24-22-03
	eClass	9	27-24-22-03

eClass	8	27-24-22-03
eClass	7.1	27-24-22-03
eClass	6	27-24-22-03
ETIM	9	EC000810
ETIM	8	EC000810
ETIM	7	EC000810
IDEA	4	3560
UNSPSC	15	32-15-17-04

Approvals / Certificates

General Product Approval



[Manufacturer Declaration](#)

[Miscellaneous](#)





[KC](#)

General Product Approval	EMV	For use in hazardous locations
--------------------------	-----	--------------------------------









[Declaration of Conformity](#)

[FM](#)

For use in hazardous locations	Marine / Shipping
--------------------------------	-------------------





[Type Examination Certificate](#)







Marine / Shipping





[NK / Nippon Kaiji Kyokai](#)







Marine / Shipping	Environment
-------------------	-------------

[CCS \(China Classification Society\)](#)



last modified: 3/12/2024 