SIEMENS

Data sheet 6ES7461-3AA01-0AA0

Figure similar

SIMATIC S7-400, interface module receiver IM 461-3 for distributed coupling up to 102 m, with C-bus

Input current	
from backplane bus 5 V DC, max.	620 mA
Power loss	
Power loss, max.	3 100 mW
Hardware configuration	
Cable length between first and last interface module, max.	102.25 m
connection method	
termination plug	6ES7461-3AA0-7AA1
Dimensions	
Width	25 mm
Height	290 mm
Depth	280 mm
Weights	
Weight, approx.	620 g

Classifications

	Version	Classification
eClass	14	27-24-22-08
eClass	12	27-24-22-08
eClass	9.1	27-24-22-08
eClass	9	27-24-22-08
eClass	8	27-24-22-08
eClass	7.1	27-24-22-08
eClass	6	27-24-22-08
ETIM	9	EC001423
ETIM	8	EC001423
ETIM	7	EC001423
IDEA	4	3564
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

CE EG-Konf. | Miscellaneous | UKCA | UL | KC | RCM

Subject to change without notice
© Copyright Siemens

EMV	For use in hazardous locations

RCM RCM IECEx ATEX FM CCC

For use in hazardous locations	Marine / Shipping

IECEx Type Examination Certificate ATEX ABS BUREAU VERITAS DNV

Marine / Shipping

LRS NK / Nippon Kaiji Kyokai PRS RINA RMRS CCS (China Classification Society)

last modified: 2/20/2025

Subject to change without notice
© Copyright Siemens