




SIMATIC S7-400, interface module IF963-RS232 with RS232 interface for PTP coupling with CP441 AB CP 441- AA05

Input current	
Current consumption, max.	15 mA
Power loss	
Power loss, typ.	0.05 W
Interfaces	
Point-to-point connection	
• Transmission rate, max.	115.2 kbit/s
• Cable length, max.	15 m
Dimensions	
Width	19 mm
Height	67 mm
Depth	87 mm
Weights	
Weight, approx.	80 g
Classifications	

	Version	Classification
eClass	14	27-24-22-08
eClass	12	27-24-22-08
eClass	9.1	27-24-22-08
eClass	9	27-24-22-08
eClass	8	27-24-22-08
eClass	7.1	27-24-22-08
eClass	6	27-24-22-08
ETIM	9	EC001423
ETIM	8	EC001423
ETIM	7	EC001423
IDEA	4	3564
UNSPSC	15	32-15-17-05

Approvals / Certificates
General Product Approval



Miscellaneous



KC



For use in hazardous locations



IECEX



ATEX

[FM](#)



CCC



IECEX

[Type Examination Certificate](#)

For use in hazardous locations

Marine / Shipping



ATEX



BUREAU
VERITAS



DNV



LRS



RINA

[CCS \(China Classification Society\)](#)

last modified:

12/8/2024