

Portable Instant Water Geyser

PRODUCT SPECIFICATION & 4-ANGLE VIEW REFERENCE SHEET

INSTANT HEATING TECHNOLOGY



TECHNICAL SPECIFICATIONS

3000W

Power Rating

230V / 50Hz

Operating Voltage

Polypropylene

Outer Body Material

1 Litre

Tank Capacity

KEY FEATURES

- **Compact Wall-Mount Design:** Rear wall-mounting slot for easy keyhole installation in kitchens or bathrooms.
- **LED Status Indicators:** Dual LED lights showing power supply and heating status at a glance.
- **4-Angle Inspection Verified:** Complete multi-view (Front, Right Side, Rear, Left Side) quality pass.
- **Shock-Proof Plastic Body:** Premium grade insulated outer body prevents electrical shock hazards.

SAFETY & OPERATION

- Always turn on water inlet supply before switching on electrical power connection.
- Equipped with automatic thermal cut-off thermostat to prevent dry heating and overheating.
- Connect to a grounded 16A wall socket using the factory-provided power cord.
- Turn off power switch immediately after hot water dispensing is complete.

IMPORTANT: Ensure water flows continuously through the outlet pipe before turning power ON. Operating without water flow will activate automatic thermal cutoff.