

## DIGITAL PODIUM

GEAR UP FOR DELIVERING **AMAZING PRESENTATIONS**

### MOTORISED TILT TOUCH SCREEN

Amazing audio out-put, makes audio lessons enriching



### BUILT-IN AUDIO SYSTEM

The inbuilt PA system not only makes voice audible, but also ensures clarity throughout the presentation



### LAPTOP STYLE KEYBOARD MOUSE

Easy to use and no need to learn new tricks while presenting



### INTEGRATED DEVICES

Built-in PC and audio system, connected in such a way that makes the use easy. Just plug-in to start the presentation



### DESIGNED WITH WHEELS

Rugged body design with caster wheels make it easy to move around



### LOCKABLE SLIDER AND CABINET

Ensures safety of your presentation notes and personal things



ATIPL DP01

DIGITAL PODIUM

## Specification

- Mild steel powder coated finished body with multiple input ports.
- Standalone power operated working lecture delivery and announcement feature.
- Inbuilt Amplifier offering high sound quality , to be interfaced with speakers and input via multiple sources
- 22-inch interactive infrared based touch display for presenter Manual Tilt Screen
- Windows operating PC – i3, 8gb ram, 512gb SSD storage, pre-loaded windows 11
- Input Channels 2x Mic 0.65mV/4.7kΩ, 1 x Aux 100mV/470 kΩ, 1 USB, 1 BLUETOOTH, 1 FM, Speaker connector2. 1
- Multimedia Amplifier Compatible with DVD, VCD, DTH, and LCD and Digital Display with remote high performance
- External Speakers to be integrated in body with amplifier and connected with amplifier offering echoless voice. Integration of speaker with amplifier must be seamless for smooth audio
- This is a general-purpose 10 Watt 2 Speakers (10 watt each speaker) which is generally used for all
- types of audio projects. It has a balanced frequency response and high efficiency. Very good high-range response
- Professional high quality PA Gooseneck Microphone 1 no , Wireless handheld – 1 no and Collar Lapel Microphone -1 no are suitable for various PA applications such as on Lecterns and Podiums, Open Conferences etc. The sleek and slender design makes the microphones unobtrusive.
- Wide frequency response.
- High front-to-back rejection for more gain before feedback.
- Built-in XLR socket.
- Frequency Response 20-18,000Hz
- Impedance 1000Ω
- Sensitivity 7.5mV/Pa
- Power Source 1.5V-9V DC
- Standard control panel for smooth connectivity – USB input, HDMI Input, VGA input,RJ45/LaN – input for internet, power socket. External ports – HDMI Out.
- Wheels mounting for movement.
- A dedicated plate must be available in the body itself in which the user can avail the charging facility directly through audio lectern

