





PRODUCT DETAILS AUTOMATIC FOUR HEAD VOLUMETRIC FILLING MACHINE



Technical Specifications		
Model		JPMF-60
Output/Hour*		2400 to 6000
Direction of Movement		Left to Right
Number of head/Syringe		4 Nos.
Fill Size**		50 ML to 1000 ML with different types of syringe
Specifications	Main Machine	1 HP / 415 Volts / 50 Hz. (1.5 HP for 1000 ml filling)
	Conveyor	0.5 HP / 415 Volts / 50 Hz.
Height of Conveyor		860 mm ± 50 mm Adjustable.
		6 Feet Length with SS 304 Slat Chain
Change parts required		(A) Syringes, (B) Nozzle, (C) Inlet & outlet hose pipe.
Input Spe	cificatio	ns
Container Neck Diameter		Minimum 18 mm
Container Size	Round Ø	28 mm to Ø 100 mm
	Re	espective Height : 58 mm to 240 mm







Salient Features

- ± 1 % Filling accuracy on single dose.
- No Bottle No Filling System
- Rigid vibration free construction for trouble free performance
- SS Elegantly matt finished body
- Elegant and easy access control panel makes it user friendly
- Minimum charge overtime from one size to another container or fill size
- Self-lubricating UHMW-PE guide profile for S.S. slat chain provides low friction & allows smooth and noiseless conveying.
- 6" Heavy Gear box for driving system.
- A/C frequency drive on control panel.
- Pneumatic bottle stopping arrangement.
- Synchronized two nos. A/c drives for main motor & conveyor belt.
- Pneumatic diving mechanism (OPTIONAL)
- MCB for over load protection, and prevent against short circuit.
- In-built pre-inspection. (OPTIONAL)

Thanking you

WEBSITE www.jackspharma.com

JACKS PHARMA MACHINERY

CHIRAG SERASIYA: +91 7600809830 (whatsapp)

> +91 8160142862 +91 9426076515

