


Hillson Footwear Pvt. Ltd.

BASE



S.NO.	NAME	SPECIFICATION
1	Opreative Standard	IS 15298 (Part-2): 2016 & EN-20345:2011
2	Design Type	Derby Low Ankle
3	Sizes Available	5 to 11 / 39 to 45
4	Weight Chart	Size 5: 820 gms, 6: 880 gms, 7: 950 gms, 8: 980 gms, 9: 1000 gms, 10: 1130 gms, 11: 1160 gms * The weight mentioned above are for reference only and may vary + -30 grams per pair
5.	Upper Components	* 100% Real Leather in Shelltac print, 1.8-2.00 mm thick & tested for chromium VI content absence * Collor - Leather & padded with high density PU Foam * Quarter Lining - Abrasion resistant Air Mesh Fabric * Tounge - PU Foam sandwiched between PU lining and airmesh * Eyelets: Anti Rust, round shaped
6	Insocks	4 mm soft Neoprene Laminated to highly abrasion resistant fabric
7	Sole	Monodensity Polyurethane with Antistatic Properties
8	Toe Cap	Steel toe cap, EN-12568:2010 Marked
9	Ideal for	Wherever safety from Falling object, oil and mild acid resistance is required majorly appreciated by Construction, Metal, automobile & chemicals, Security & Soft Industry
10	USP	This entry level standardized safety footwear is best suited for those who want it simple and perfectly safe. A high performer in its category where so many non compliant options are flooded in the market
<p>IS : 15298 : PART 2</p>  <p>CM/L-9954209</p>		