



## GBNU.EX16332 Dry-chemical Extinguishing Agents for Special Application

[Page Bottom](#)

---

### Dry-chemical Extinguishing Agents for Special Application

[See General Information for Dry-chemical Extinguishing Agents for Special Application](#)

**FOAMTECH ANTIFIRE CO**

EX16332

PLOT 18

SECTOR 1B

SIDCUL BHEL COMPLEX

HARIDWAR, UA 249401 INDIA

Model Foamtech Antifire Flamax Brand Firex dry chemical Classified for physical properties and special applications on Class B flammable liquids having a minimum application density required to be applied to the surface of Class B flammable liquids of 0.107 lb/ft<sup>2</sup> (0.52 kg/m<sup>2</sup>).

[Last Updated](#) on 2014-03-06

---

[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2014 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2014 UL LLC".