

VACUUM OVEN (LI-OV-6)

APPLICATION :

Heat-sensitive material can be dried in the **Vacuum Oven** at low temperatures, and at the same time the drying time is considerably reduced..



FEATURES :

- Double walled construction.
- Inside made of SS and outer made of MS duly power coated.
- Gap between two walls is duly filled with high grade glass wool to avoid thermal loss.
- Temperature range above ambient 5°C to 150°C.
- Controlled by thermostat (Optional : Digital temp. indicator-cum-controller).
- Fitted with vacuum gauge, transparent glass window door, two shelf.

TECHNICAL SPECIFICATIONS :

Chamber Size (HxWxD)	In Inches	No. of Shelves	Capacity (approx)
300mm x 300mm x 300mm	12" x 12" x 12"	2	28
350mm x 350mm x 350mm	14" x 14" x 14"	2	45
400mm x 400mm x 400mm	16" x 16" x 16"	2	65
450mm x 450mm x 450mm	18" x 18" x 18"	2	95
600mm x 450mm x 450mm	24" x 18" x 18"	2	125
600mm x 600mm x 600mm	24" x 24" x 24"	2	224
900mm x 600mm x 450mm	36" x 24" x 18"	2	252
900mm x 600mm x 600mm	36" x 24" x 24"	2	336
900mm x 900mm x 900mm	36" x 36" x 36"	3	720

OPTIONALS :

- Digital temp. indicator-cum-controller.

Models, Features and Specifications subject to change without notice.